NOTE: ALL MATERIAL COMPLIANT ROHS STANDARD

	REVISION INFORMATION						
	Rev.	Rev. Date	Modified By	Brief Description			


E-LIT PANEL UL 2'X4'


The UL listed edge light panel is designed to the most energy saving panel with 130lm/w max, 100,000 hours long life, and 90% uniformity across the emitting surface.

UL, FCC, DLC, DLC Premium Listed.

PART NAME

The panel enables customers to recover initial investment quickily and greatly reduce the maintenance cost.







Input Power 76W

Product Dimensions 2'x4'(604x1214mm) **LED Driver Input** 100-277VAC 50/60Hz

Driver Output Data 25-38Vdc / 1030ma /36W

Driver / Connection >Fixed Driver

Over Load / Short Circuit Protection

Surge Protection Class >1KV/ Class II

Color temperature NW Natural white 5000K

LED Type 26X46mil Chip

LED Quantity 216 Pcs

30,000 Hours/5Years Average Life

IP 20 IP Grade

QT'Y

UNIT

Certification

• UL, DLC/DLC Premium, FCC, CUL Lighting Fact

3			Unless sp
2			Unless sp drawing,t per the fo
1		·	.x

SPECIFICATION DESCRIPTION

specified on the .tolerances are ollows: +1

+0.2 +0.05



DRAWN BY	DATE: 2016/09/05	DESCRIPTION:				
		2'4' LED PANEL LIGHT				
CHECKED BY	SHEET 1of1	ITEM NO. 210827				
APPROVED BY	SCALE 1:1	REV. 00	UNIT:mm	—		