



NI2VD24-VVF



**Mechanical IR
Cut Filter (ICR)**

FEATURES

- **HD TVI 1920 x 1080 @ 30fps**
- 2 Megapixel High Resolution
- 1/3" Progressive Scan CMOS
- 2.8~12mm Vari-Focal Lens
- 0.014 Lux @ F1.4 (AGC ON), 0 Lux with IR
- 24 IR LED
- IR distance up to 100ft / 30m
- Mechanical IR Cut Filter (ICR)
- 3D DNR, Digital WDR
- Max. 5.5W
- 12V DC / PoE (802.3af)
- IP66 Rating

SPECIFICATIONS

Model	NI2VD24-VVF
Image Sensor	1/3" Progressive Scan CMOS
Horizontal Resolution	2.0MP
Max. Image Resolution	1920 x 1080
Frame Rate	60Hz: 30fps (1920×1080) 50Hz: 25fps (1920×1080)
Shutter Time	1/25s ~ 1/100,000s
Minimum Illumination	0.014 Lux @ F1.4 (AGC ON), 0 Lux with IR
Day & Night	Built-in Mechanical IR Cut Filter (ICR)
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
IR LED	24pcs IR
IR Distance	100ft / 30m
Lens Type	2.8~12mm Vari-Focal Lens (Angle of view: 113°~33.8°)
Lens Mount	Φ 14
Angle Adjustment	Pan: 0°~355° ; Tilt: 0°~75° ; Rotation: 0°~355°
Video Compression	H.264 / MJPEG
H.264 Codec Profile	Main Profile
Bit Rate	32 Kbps ~ 16 Mbps
Audio Compression	G.711/G.726/MP2L2
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.726)/ 32~128Kbps(MP2L2)
Dual Stream	Yes
Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
ROI	Support
BLC	Yes, Zone Optional
Network Storage	NAS
Alarm Trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, Storage full, Storage error
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
System Compatibility	ONVIF, PSIA, CGI, ISAPI
General Functionalities	User Authentication, Watermark
Communication Interface	1 RJ45 10M / 100M ethernet port
On-board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB
Audio Input / Output	1 / 1
Alarm Input / Output	1 / 1
Power Source	12 VDC ± 10%, PoE (802.3af)
Power Consumption	Max. 5.5W
Impact Protection	IEC60068-275Eh, 50J; EN50102, up to IK10
IP Rating	IP66
Operating Temperature	-22°F ~ 140°F / -30°C ~ 60°C
Humidity	95% or less (non-condensing)
Dimension	5.6(Ø) x 3.9(H) inches / 142(Ø) x 99.9(H) mm
Net Weight	2.2 lbs / 1 kg

*Specifications and appearance are subject to change without notice