



VERSION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description









- NOTES:
- 1.Operation Temperature:-40℃～+85℃.
 - 2.Electrial Characteristics:
 - 2.1>Rated Current : 125V AC,1.5A@25℃.
 - 2.2>Contact Resistance : 20mΩ Max.
 - 2.3>Insulation Resistance:500MΩ Min,100V DC/min.
 - 2.4>Voltage Proof: 1000V AC/1 minute no breakdown
 - 3.Mechanical Characteristics:
 - 3.1>Insertion Force & Withdrawal Force : 30N Max.
 - 3.2>Durability:750 cycles Min.
 - 4.Environmental compliance:
 - 4.1>the products are compliant with the RoHS, and REACH etc.
 - 5.Compatible wire gauge:28AWG
Compatible outer diameter:3.5~3.8MM

1	Modular Plug	Contacts	8PCS	2 Prongs ☐ 3 Prongs ☒	G/F'' ☐ 1u'' ☐ 3u'' ☐ 6u'' ☐ 15u'' ☐ 30u'' ☐ 50u'' ☒ other ☐	Brass ☒ ☐ Phosphor copper
		Housing	1PC	transparent PC		94V-2 ☒ 94V-0 ☐
NO.	NAME		QTY	DESCRIPTION		MATERIAL

DRAWN BY FW	DATE: 2026/04/29	DESCRIPTION: RJ45 Cat6A Tangle Free Plug 50Micron Gold Plated 28AWG 100pk
CHECKED BY ACE	SHEET 1 of 3	ITEM NO. 101235
APPROVED BY	SCALE 1:1	REC. 00 UNIT: mm



VERSION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description



DRAWN BY FW	DATE: 2026/04/29	DESCRIPTION: RJ45 Cat6A Tangle Free Plug 50Micron Gold Plated 28AWG 100pk	
CHECKED BY ACE	SHEET 2 of 3	ITEM NO.	101235
APPROVED BY	SCALE 1:1	REC. 00	UNIT: mm

