

USB 3.1 Type-C to USB3.0 x 2+ HDMI+ Micro SD+SD +Type-C Charging Adapter

User Manual



Contents

1.0 INTRODUCTION	1
2.0 FEATURES	1
3.0 SPECIFICATIONS	2
4.0 PACKAGE CONTENTS	2
5.0 OPERATION	2
6.0 CONNECTION DIAGRAM.....	3

USB 3.1 Type-C to USB3.0 x 2+HDMI+ Micro SD+SD +Type-C Charging Adapter

DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

1.0 INTRODUCTION

This is a USB-C to USB 3.0 Hub, The USB3.0 port allows you to connect a USB device or another hub to the host computer, the Micro SD and SD/MMC port allows you to access the external memory of the host PC. the HDMI port (DP Altmode) allows you to connect an HDMI monitor so that you can watch videos or slideshows together on a big screen. the USB-C female port can charge for the host computer and supply power for the hub simultaneously.

2.0 FEATURES

- Support USB 3.0 super speed (5Gbps) transmission, downward compatible USB2.0
- Support HDMI video resolution up to 4KX2K@30Hz
- USB 3.0 port supports to charge and transmit data for the USB device simultaneously
- Support to access external memory for the host computer
- Support twisted pair crossover detection and auto-correction
- USB-C female port can charge for Macbook or Google new Chromebook Pixel and other USB-C supported devices and supplies power for the hub simultaneously
- USB-C female port supplies power up to 60W (20V/3A)

- Multiple USB-C interfaces support plug and play, hot swap
- Easy to use and carry

3.0 SPECIFICATIONS

Input/Output Connector	
Input	USB-C Male x1 USB-C Female x1for charging
Output	USB 3.0 Female x2 HDMI Female x1 Micro SDX1 SD/MMCX1
Warranty	
Limited Warranty	1 Year
Environmental	
Operating Temperature	0 °C to +45°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	5% to 90% RH (no condensation)
Power Supply	
USB3.0 Port	UP to 5W (5V/1A)
USB-C Female Port	Up to 60W (20V/3A)
Regulatory Approvals	
Certifications	FCC,CE
Accessory Adapter	
User Manual	English Version

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 OPERATION

- 1) Connect the USB-C male port of this product to Macbook or Chromebook
- 2) Connect the USB 3.0 output of this product to a USB 3.0/USB 2.0 device
- 3) Connect HDMI output of this product to HDTV with one HDMI cable

- 4) Insert Micro SD, SD/MMC card into the responding slots
- 5) Connect the USB-C charging port, it can charge for the host computer and support this adapter to work simultaneously

6.0 CONNECTION DIAGRAM

