



SHS-7540DN
SHS-7540DNP
SSS-7420
SSS-7420P



- 1/3" Sony Super HAD CCD
- 540 TV Lines, HQ-1 DSP SHS-7540DN/SHS-7540DNP
420 TV Lines SSS-7420/SSS-7420P
- 3.6mm Standard Lens
- 0.5 Lux @ F2.0 SHS-7540DN/SHS-7540DNP
0.3 Lux @ F2.0 SSS-7420/SSS-7420P
- 12V DC

Day & Night Feature Only Available for SHS-7540DN/SHS-7540DNP

Smoke Detector Covert

Color Camera



SPECIFICATIONS

FC CE Made in Taiwan

| | | | | |
|-------------------------|--|-------------------|-------------------|-------------------|
| Model Number | SHS-7540DN | SHS-7540DNP | SSS-7420 | SSS-7420P |
| TV System | NTSC | PAL | NTSC | PAL |
| Image Sensor | 1/3" Sony Super HAD CCD | | | |
| DSP | Sony HQ-1 | | Sony | |
| Resolution | 540 TV Lines | | 420 TV Lines | |
| Video Output | 1.0V p-p / 75Ω | | | |
| Total Pixels | 811(H) x 508(V) | 795(H) x 596(V) | 537(H) x 505(V) | 537(H) x 597(V) |
| Scan System | 2:1 Interlace | | | |
| Synchronization | Internal | | | |
| Minimum Illumination | 0.5 Lux @ F2.0 Color mode automatically switches to B/W mode under 2.0 Lux | | 0.3 Lux @ F2.0 | |
| Signal to Noise Ratio | More than 50dB (ACG OFF) | | | |
| Gain Control | Full Auto | | | |
| White Balance | AWB | | | |
| Back Light Compensation | Full Auto | | | |
| Electronic Shutter | 1/60~1/100,000sec | 1/50~1/100,000sec | 1/60~1/100,000sec | 1/50~1/100,000sec |
| Lens | 3.6mm Standard Lens | | | |
| Power Supply | 12V DC | | | |
| Power Consumption | 1.7W / 142mA | | 1.1W / 92mA | |
| Operation Temperature | Working: -10° ~ +50°C Humidity: 85% RH or less | | | |
| Dimensions | 106.5(W) x 60.5mm(L) | | | |
| Weight | 220g | | | |

*Specifications and appearance are subject to change without notice

DIMENSIONS

